MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION AND COMPANY DETAILS

PRODUCT NAME: ATELIER INTERACTIVE ACRYLICS

(Prop 65 Colors. See Section 15 for additional information.)

(All information the same for all sizes.)

COMPANY NAME: CHROMA, INC. ADDRESS: 205 Bucky Drive

Lititz, PA 17543 U.S.A.

PHONE: 800-257-8278 **FAX:** 717-626-9292

WEBSITE: www.chromaonline.com

DATE PREPARED: December 23, 2013

EMERGENCY: If swallowed, call your poison control center at 1-800-222-1222.

Seek medical assistance for further treatment, observation and support, if necessary.

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration
WATER	7732-18-5	PROPRIETARY
VARIOUS PIGMENTS		PROPRIETARY
ACRYLIC EMULSION		PROPRIETARY
ACRYLIC THICKENERS		PROPRIETARY
PRESERVATIVE		PROPRIETARY
ALKALINE STABILIZER		PROPRIETARY

SECTION 3 – HAZARDS IDENTIFICATION

Hazardous Ingredients: NONE

Primary Routes of Entry: SKIN ABSORPTION, INHALATION, INGESTION

Carcinogen Listing: IARC MONOGRAPH, OSHA

Health Hazards Acute: MAY CAUSE SLIGHT IRRITATION TO EYES OR SKIN OR

IF INHALED

Health Hazards Chronic: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO

THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH

DEFECTS AND OTHER REPRODUCTIVE HARM.

Signs & Symptoms of Exposure: NONE

Medical Conditions Generally Aggravated by Exposure: NONE

Prop 65 Colors - Atelier Interactive Acrylics

Page 1 of 4 MSDS Date 8/14

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

Health Effects:

Acute: Eye DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION

Skin PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION

Inhaled INHALATION OF VAPOR MAY CAUSE SLIGHT IRRITATION

Chronic NONE ALLOCATED

SECTION 4 – FIRST AID MEASURES

Skin WASH SKIN WITH SOAP AND WATER OR USE A PRODUCT SPECIFICALLY

FORMULATED FOR WATER BASED PAINT REMOVAL. IF IRRITATION PERSISTS SEEK MEDICAL HELP.

Eye CHECK FOR AND REMOVE ANY CONTACT LENSES.

FLUSH EYES UP TO 15 MINUTES WITH WATER, HOLDING EYE LIDS OPEN.

IF IRRITATION PERSISTS SEEK MEDICAL HELP.

Inhaled IF PERSON IS SHOWING ADVERSE EFFECTS, REMOVE PERSON TO FRESH AIR.

SEEK MEDICAL HELP IF SYMPTOMS OCCUR.

Ingestion IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK.

NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SEEK MEDICAL HELP IF SYMPTOMS OCCUR.

IF SWALLOWED, CALL YOUR POISON CONTROL CENTER AT 1-800-222-1222.

SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT, IF NECESSARY.

Advice to Doctor:

THIS PRODUCT CARRIES THE A.P. SEAL, CONFORMS TO ASTM D4236, AND IS CERTIFIED NON-TOXIC BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, HANSON, MA 02341 USA.

SECTION 5 – FIRE FIGHTING MEASURES

Fire / Explosion Hazard:

Flash Point (Method):

Auto-Ignition Temperature:

Flammability Limits In Air (% by Volume):

NONE

N/A

N/A

LOWER EXPLOSIVE LIMIT (LEL): UNKNOWN UPPER EXPLOSIVE LIMIT (UEL): UNKNOWN

Extinguisher Media: CARBON DIOXIDE, WATER SPRAY, FOAM OR

DRY CHEMICAL

Special Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS AND

FULL PROTECTIVE CLOTHING

Unusual Fire & Explosion Hazards: DECOMPOSITION AND COMBUSTION PRODUCTS MAY

BE TOXIC.

Extinguishing Media:

THIS PRODUCT IS NOT FLAMMABLE. USE FIRE-EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING MATERIALS.

Prop 65 Colors - Atelier Interactive Acrylics

Page 2 of 4 MSDS Date 8/14

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Leak & Spill Procedures:

TAKE CARE FLOOR SURFACE WILL BE SLIPPERY AT SITE OF SPILLAGE.

FOR MINOR SPILLS, MOP-UP WITH RAGS AND DISPOSE OF.

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS (SAND, SAWDUST, ETC.) AND TRANSFER TO CONTAINERS FOR DISPOSAL.

DO NOT CONTAMINATE WATER SOURCES OR SEWER.

SECTION 7 – HANDLING AND STORAGE

Handling Procedures & Equipment:

AVOID SKIN AND EYE CONTACT.

WASH HANDS AFTER USE.

Storage Requirements:

STORE AT ROOM TEMPERATURE.

KEEP FROM FREEZING.

RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 34° F AND 122 °F (1° C AND 50 °C).

SECTION 8 - EXPOSURE CONTROL / PERSONAL PROTECTION

Protective Equipment:

Respiratory Protection (Specific Type): NONE NEEDED UNDER NORMAL CONDITIONS OF USE

DO NOT SAND OR SPRAY APPLY

Protective Gloves:

Eye Protection:

Other Protective Equipment:

NOT REQUIRED

NOT REQUIRED

Hygienic Work Practices: AS WITH ANY WATER BASED PRODUCT

Ventilation To Be Used:

Local Exhaust: N/A
Mechanical (General): N/A
Special: N/A
Other (Specify): N/A

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 215°-275°F Specific Gravity (H2O=1): NOT KNOWN

Vapor Pressure: NOT KNOWN Melting Point: NOT KNOWN

Specific Vapor Density (AIR=1): LIGHTER THAN AIR Evaporation Rate: SLOWER THAN ETHER

Solubility in Water: COMPLETELY SOLUBLE Reactivity in Water: NOT KNOWN

Appearance & Odor: IMPASTO ACRYLIC PAINTS IN ASSORTED COLORS.

Prop 65 Colors - Atelier Interactive Acrylics

Page 3 of 4 MSDS Date 8/14

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

SECTION 10 – STABILITY AND REACTIVITY

Stability: STABLE
Conditions To Avoid: N/A
Incompatibility (Materials to Avoid): NONE
Hazardous Decomposition Products: NONE

Hazardous Polymerization Products: NONE Conditions To Avoid: N/A

SECTION 11 – TOXICOLOGICAL INFORMATION

The toxicological information for the components is: NON-TOXIC

THIS PRODUCT CARRIES THE A.P. SEAL, CONFORMS TO ASTM D4236, AND IS CERTIFIED NON-TOXIC BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, HANSON, MA 02341 USA.

SECTION 12 – ECOLOGICAL INFORMATION

NOT REGARDED AS DANGEROUS FOR THE ENVIRONMENT.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

DISPOSE OF IN ACCORDANCE WITH LOCAL AND NATIONAL REGULATIONS FOR INERT NON-HAZARDOUS WASTE MATERIAL.

SECTION 14 – TRANSPORT INFORMATION

NON-HAZARDOUS FOR RAIL, ROAD, SEA AND AIR TRANSPORT.

SECTION 15 – REGULATORY INFORMATION

THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS AND OTHER REPRODUCTIVE HARM.

THIS PERTAINS <u>ONLY</u> TO THE COLORS LISTED BELOW, WHICH REQUIRE THE STATE OF CALIFORNIA PROP 65 WARNING.

CADMIUM ORANGE, CADMIUM RED MEDIUM, CADMIUM RED LIGHT (SCARLET), CADMIUM YELLOW DEEP, CADMIUM YELLOW LIGHT, CADMIUM YELLOW MEDIUM, CARBON BLACK, MARS BLACK, TITANIUM DIOXIDE (AIRBORNE, UNBOUND PARTICLES OF RESPERIBLE SIZE ONLY), COBALT TURQUOISE LIGHT, CERULEAN BLUE, COBALT GREEN, COBALT BLUE, RED BLACK, GREEN BLACK, BLUE BLACK, BROWN BLACK, OLIVE GREEN, TONING GREY PINK, ORANGE AND PAYNES GREY

SECTION 16 – OTHER INFORMATION

THIS PRODUCT DOES NOT CONTAIN EGG, DAIRY, WHEAT, GLUTEN, SOY OR PEANUT PRODUCTS, BY-PRODUCTS OR DERIVATIVES.

THIS PRODUCT DOES NOT CONTAIN LATEX MATERIALS OR ANIMAL DERIVED INGREDIENTS.		