SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION AND COMPANY DETAILS

PRODUCT NAME:	ATELIER INTERACTIVE ACRYLICS (Non Prop 65 Colors. See Section 15 for additional information.) (All information the same for all sizes.)
COMPANY NAME:	CHROMA, INC.
ADDRESS:	205 Bucky Drive
	Lititz, PA 17543 U.S.A.
PHONE:	800-257-8278
FAX:	717-626-9292
WEBSITE:	www.chromaonline.com
DATE PREPARED:	September 12, 2016
EMERGENCY:	If swallowed, call your poison control center at 1-800-222-1222. Seek medical assistance for further treatment, observation and support, if necessary.

SECTION 2 – HAZARDS IDENTIFICATION

Hazardous Ingredients: NONE

Primary Routes of Entry:	NOT HAZARDOUS
Carcinogen Listing:	NOT LISTED
Health Hazards Acute:	NONE
Health Hazards Chronic:	NONE
Signs & Symptoms of Exposure:	NONE
Medical Conditions Generally Aggravated by Exposure:	NONE

Health Effects:

Acute:	Eye	DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION
	Skin	PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION
	Inhaled	INHALATION OF VAPOR MAY CAUSE SLIGHT IRRITATION
	Chronic	NONE ALLOCATED

CAS No.

7732-18-5

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name WATER VARIOUS PIGMENTS ACRYLIC EMULSION ACRYLIC THICKENERS PRESERVATIVE ALKALINE STABILIZER

Non Prop 65 Colors – Atelier Interactive Acrylics

Page 1 of 4 SDS Date 9/16

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

SECTION 4 – FIRST AID MEASURES

Skin	WASH SKIN WITH SOAP AND WATER OR USE A PRODUCT SPECIFICALLY FORMULATED FOR WATER BASED PAINT REMOVAL. IF IRRITATION PERSISTS SEEK MEDICAL HELP.
Eye	CHECK FOR AND REMOVE ANY CONTACT LENSES. FLUSH EYES UP TO 15 MINUTES WITH WATER, HOLDING EYE LIDS OPEN. IF IRRITATION PERSISTS SEEK MEDICAL HELP.
Inhaled	IF PERSON IS SHOWING ADVERSE EFFECTS, REMOVE PERSON TO FRESH AIR. SEEK MEDICAL HELP IF SYMPTOMS OCCUR.
Ingestion	IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL HELP IF SYMPTOMS OCCUR. IF SWALLOWED, CALL YOUR POISON CONTROL CENTER AT 1-800-222-1222.

SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT, IF NECESSARY.

Advice to Doctor:

THIS PRODUCT CARRIES THE A.P. SEAL, CONFORMS TO ASTM D4236, AND IS CERTIFIED NON-TOXIC BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, HANSON, MA 02341 USA.

SECTION 5 – FIRE FIGHTING MEASURES

Fire / Explosion Hazard:	NONE
Flash Point (Method):	N/A
Auto-Ignition Temperature:	N/A
Flammability Limits In Air (% by Volume):	N/A
LOWER EXPLOSIVE LIMIT (LEL):	UNKNOWN
UPPER EXPLOSIVE LIMIT (UEL):	UNKNOWN
Extinguisher Media:	N/A
Special Fire Fighting Procedures:	N/A
Unusual Fire & Explosion Hazards:	N/A

Extinguishing Media:

THIS PRODUCT IS NOT FLAMMABLE. USE FIRE-EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING MATERIALS.

Non Prop 65 Colors – Atelier Interactive Acrylics

Page 2 of 4 SDS Date 9/16

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Leak & Spill Procedures:

TAKE CARE FLOOR SURFACE WILL BE SLIPPERY AT SITE OF SPILLAGE.

FOR MINOR SPILLS, MOP-UP WITH RAGS AND DISPOSE OF.

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS (SAND, SAWDUST, ETC.) AND TRANSFER TO CONTAINERS FOR DISPOSAL.

DO NOT CONTAMINATE WATER SOURCES OR SEWER.

SECTION 7 – HANDLING AND STORAGE

Handling Procedures & Equipment:

AVOID SKIN AND EYE CONTACT.

WASH HANDS AFTER USE.

Storage Requirements:

STORE AT ROOM TEMPERATURE.

KEEP FROM FREEZING.

RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 34° F AND 122 °F (1° C AND 50 °C).

N/A

N/A

N/A

N/A

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

Protective Equipment:

Respiratory Protection (Specific Type):

Protective Gloves: Eye Protection: Other Protective Equipment: Hygienic Work Practices:

Ventilation To Be Used:

Local Exhaust: Mechanical (General): Special: Other (Specify):

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 215°-275°F Vapor Pressure: NOT KNOWN Specific Vapor Density (AIR=1): LIGHTER THAN AIR Solubility in Water: COMPLETELY SOLUBLE Specific Gravity (H2O=1): NOT KNOWN Melting Point: NOT KNOWN Evaporation Rate: SLOWER THAN ETHER Reactivity in Water: NOT KNOWN

Appearance & Odor: IMPASTO ACRYLIC PAINTS IN ASSORTED COLORS.

Non Prop 65 Colors – Atelier Interactive Acrylics Page 3 of 4 SDS Date 9/16 While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

NONE NEEDED UNDER NORMAL CONDITIONS OF USE TAKE PRECAUTIONS WHEN SANDING OR SPRAY APPLYING NOT REQUIRED NOT REQUIRED AS WITH ANY WATER BASED PRODUCT

SECTION 10 – STABILITY AND REACTIVITY

Stability:	STABLE
Conditions To Avoid:	N/A
Incompatibility (Materials to Avoid):	NONE
Hazardous Decomposition Products:	NONE
Hazardous Polymerization Products:	NONE
Conditions To Avoid:	N/A

SECTION 11 – TOXICOLOGICAL INFORMATION

The toxicological information for the components is: NON-TOXIC

THIS PRODUCT CARRIES THE A.P. SEAL, CONFORMS TO ASTM D4236, AND IS CERTIFIED NON-TOXIC BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, HANSON, MA 02341 USA.

SECTION 12 – ECOLOGICAL INFORMATION

NOT REGARDED AS DANGEROUS FOR THE ENVIRONMENT.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Methods:

DISPOSE OF IN ACCORDANCE WITH LOCAL AND NATIONAL REGULATIONS FOR INERT NON-HAZARDOUS WASTE MATERIAL.

SECTION 14 – TRANSPORT INFORMATION

NON-HAZARDOUS FOR RAIL, ROAD, SEA AND AIR TRANSPORT.

SECTION 15 – REGULATORY INFORMATION

THIS PERTAINS TO ALL COLORS <u>OTHER THAN</u> THOSE REQUIRING THE STATE OF CALIFORNIA PROP 65 WARNING WHICH INCLUDE:

CADMIUM ORANGE, CADMIUM RED MEDIUM, CADMIUM RED LIGHT (SCARLET), CADMIUM YELLOW DEEP, CADMIUM YELLOW LIGHT, CADMIUM YELLOW MEDIUM, CARBON BLACK, MARS BLACK, CHROMIUM GREEN OXIDE, TITANIUM DIOXIDE (AIRBORNE, UNBOUND PARTICLES OF RESPERIBLE SIZE ONLY), COBALT TURQUOISE LIGHT, CERULEAN BLUE, COBALT GREEN, COBALT BLUE, RED BLACK, BLUE BLACK, GREEN BLACK, BROWN BLACK, TONING GRAY PINK, ORANGE, PAYNES GRAY

SECTION 16 – OTHER INFORMATION

THIS PRODUCT DOES NOT CONTAIN EGG, DAIRY, WHEAT, GLUTEN, SOY OR PEANUT PRODUCTS, BY-PRODUCTS OR DERIVATIVES.

THIS PRODUCT DOES NOT CONTAIN LATEX MATERIALS OR ANIMAL DERIVED INGREDIENTS.

Non Prop 65 Colors – Atelier Interactive Acrylics

Page 4 of 4 SDS Date 9/16

While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.